

Mistblower Service & Maintenance

The Sprayer

HOURS IN SERVICE						MAINTENANCE ACTION
1,000 or Annually*	250	100	50	10		
						SPRAY CIRCUIT Run machine and check for leaks
					Check & Clean	FILTERS Check and clean suction and in-line filters
						NOZZLES Check and clean all nozzles
					Grease & Oil	PTO SHAFT Grease universal joints of PTO shaft
						PUMP SUPPORT Check the pump support and retighten all bolts
					Check & Clean	TYRES Check tyre pressure
						PTO SHAFT Check condition of PTO shaft protection guard
					Tighten	WHEELS Retighten wheel nuts
					Grease	PUMP Grease pump
					& Oil	PTO SHAFT Grease the spline of the PTO shaft
					Grease & Oil	DRAWBAR Grease the drawbar
					Check & Clean	SPRAY CIRCUIT Check all the hoses in the spray circuit
					Tighten	GEARBOX SUPPORT Check the gearbox support and re-tighten all bolts
					Grease	WHEELS Check the wheel bearings
					& Oil	WHEELS Grease the wheel hubs
					Check & Clean	LIGHTS Check wiring to the lights
						GEARBOX Change the gearbox oil
					Grease & Oil	FAN CLUTCH Dismantle, check, clean and lubricate the fan clutch
	*Whichever comes first					THROUGH-SHAFT Grease the shaft running through the main tank and its universal joints
DATE DEALER DETAILS TECHNICIAN						DATE TECHNICIAN NAME SIGNATURE